



PHYSICAL PROPERTIES & PERFORMANCE

| | |
|--|--|
| Appearance: Black Solid | Maximum VOC: Less than 10 g/L |
| Application Temperature: 32° F and rising. | Specific Gravity: n/a |
| Viscosity: n/a | Weight Per Gallon: Approximately 5 lbs. . per gallon |
| Color: Black | Consistency: Solid |
| Boiling Point: 225° F | Cure Time (50% relative humidity, 70° F): 20 minutes |
| Freeze ability: n/a | Container Size & Weight: Approximately 2 lbs. |

FEATURES

Latex•ite®PLI-STIX® **Permanent Asphalt / Concrete Crack Filler** is the only **PERMANENT** solution to cracks on the marketplace. It is the same product seen on highways and roads but the only difference is **YOU CAN APPLY IT** and don't need a 200 gallon melter to do it! Latex•ite®PLI-STIX® is permanent because it is applied with heat (a simple hand held torch) and it bonds to the sidewalls of the crack. Cracks open up because they expand and contract with freeze/thaw cycles - but Latex•ite®PLI-STIX® will expand and contract right along with Mother Nature! (Note: Pli-Stix® and Crack-Stix® is the same product. Pli-Stix® comes in 30ft rolls, while Crack-Stix® comes in a 125 ft. roll.)

- **Only permanent crack filler on the marketplace.**
- **Fills cracks up to 1/2".**
- **Hot applied "rope-like" filler bonds to sidewalls.**
- **Low VOC's**

SURFACE PREPARATION

Latex•ite®PLI-STIX® is a simple and clean process. Before applying the product, it is important to thoroughly clean out the crack and remove any loose debris. Use a screwdriver and whisk broom. Rinsing the crack and allowing it to dry will give you the best results.

APPLICATION

Now you are ready to install the Latex•ite®PLI-STIX®. Simply place the Latex•ite®PLI-STIX® into the crack (do not remove the plastic wrap from the Latex•ite®PLI-STIX®). The Latex•ite®PLI-STIX® must be inside the crack so we recommend pushing the Latex•ite®PLI-STIX® into the crack using a screwdriver. (*Note: If the crack is not as wide as the 1/2" Latex•ite®PLI-STIX®, we recommend stretching the Latex•ite®PLI-STIX® out...you can leave it in the sun for a while to make it easier to stretch. You can also splice it with a razor blade). Once it's in simply light your torch (we recommend a Bernzomatic hand-held torch) and apply

direct flame to the Latex•ite®PLI-STIX® until it liquefies - this should take about 20 - 30 seconds. Allow the Latex•ite®PLI-STIX® to set up for 20 minutes. Latex•ite®PLI-STIX® can be sealed over once properly set up.

PRECAUTIONS

Avoid applying when temperatures drop below 32° F. Allow all repaired surfaces to cure 24 hours prior to sealing. When transporting this product, ensure that the container is secured and the lid is secure. Protective clothing and eyewear should be used during application.

CLEAN UP & STORAGE

To remove Latex•ite®PLI-STIX® heat and scrape off excess material. Do not store in areas above 110°F. Product is non-hazardous.

!!!CAUTION!!!

Latex•ite®PLI-STIX® is for exterior use only. Keep out of reach of children. Keep container capped when not in use. Non-flammable. This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

Emergency & First Aid Procedures:

Eyes: Immediately flush with clean water for 15 minutes while holding eyelids open; consult a physician.

Inhalation: If overcome by mist or vapor, remove from exposure immediately; call a physician. If breathing is stopped or irregular, start resuscitation, administer oxygen.

Skin: Remove any contaminated clothing and wash skin with soap and warm water. Vegetable or mineral oil can remove dry material.

Ingestion: DO NOT INDUCE VOMITING even though vomiting may occur. If vomiting occurs, keep head below hips to prevent aspiration of liquid into the lungs. Get immediate medical attention.

WARRANTY AND DISCLAIMER

There are no express warranties which extend beyond the description on the face hereof. MANUFACTURER DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY, OR OF FITNESS FOR ANY PARTICULAR PURPOSE. Since seller cannot control the manner of use of its products after their sale, seller will not be responsible for any consequential or indirect damages. Rather, seller will, at its options, either replace the goods sold or refund the purchase price. No warranties will apply if the goods are in any way altered or modified after delivery by seller. This warranty does not include labor or cost of labor for the application or consequential damages. This warranty gives you specific rights and you may also have other rights which may vary from state to state.