



Your blacktop driveway takes a beating from traffic, weather, freeze/thaw cycles and constant UV exposure. Until now there has only been two choices: re-seal or re-pave. Although traditional driveway sealers do a good job of beautifying and offering protection, no alternative has been offered that will give your driveway the look of new pavement with all the same protection benefits...at a reasonable cost. This is exactly what we have accomplished with Lift™! Lift™ is a low VOC, water based poly-acrylic formula that is **four times** thicker than traditional blacktop driveway sealers. Lift™ will give your driveway a new, uniform, slip resistant satin black micro-surface that will cover up hairline cracks and minor imperfections while slowing down your driveway's pace of aging and oxidation.

APPLICATION INSTRUCTIONS

Where to Use: Lift™ is to be used on blacktop pavement (not concrete). If new pavement allow to cure 6 months or one full season prior to applying. Pavement can be either sealed or unsealed. Remember, for best results use the specially designed Lift™ FLEX™ Applicator. Use of roller, brush or non-Lift™ squeegees VOIDS the warranty.

Preparation: Pavement must be clean, dry and free of any dirt, oil, grease, pine sap before application. Power washing recommended but if not available sweep and clean off driveway and rinse away dirty residue with water.

Repairs: Although Lift™ will provide a uniform surface we still do recommend repairing any large cracks (1/2" or greater), depressions and potholes. Cracks can be filled with either our Pli•Stix®/Crack-Stix® product, liquid crack fillers or Trowel Patch®. Fill depressions with Trowel Patch®. Allow cracks and depression repairs to cure 24 hours prior to applying Lift™. Potholes should be filled with a stone patch – we recommend our Super Patch® (allow 2 weeks to cure before applying Lift™ on top of pothole repairs so oils can evaporate).

Lift™ Application: Use product when air and surface temperature above 50°F and no rain or colder weather in forecast for at least 24 hours. Determine the appropriate number of pails necessary (see coverage chart). Make sure you have the FLEX™ Applicator. Open pails and stir to even consistency – when not in use you can place lid back on top of pail – plan on doing entire project in one continuous application without starting and stopping (to prevent color shading). If driveway is extremely hot you can mist the pavement off and apply product. If you have pavers that line the driveway or a concrete curb at end you may want to first edge the driveway with Lift™ using a wallpaper brush.

Always work with gravity and pour out 1/3 of pail and work product by pulling squeegee back and forth across driveway. **Tip:** For an even finish (no ridges) slightly twist the squeegee towards your chest with top hand as you pass across driveway slightly overlapping bead. It is your right hand as you go left to right (It is your left hand as you go right to left). Apply only slight down pressure. Complete entire driveway at one time in order to prevent color shading. When completed, block off driveway with empty pails. Humid or cloudy conditions will prevent drying and curing time. Check surface prior to vehicle traffic.

Coverage: Coverage rates are determined using Lift™ FLEX™ Applicator (Use of roller, brush or non-Lift™ squeegees VOIDS the warranty). Approximate coverage: 200 square feet per 4.75 gallon pail. Note: Less coverage will be obtained when applying on rough/porous/unsealed surface: approximately 125 - 150 square feet.

Clean-Up: While wet, clean tools with soap and water. If dry, use any citrus based cleaner and scrub.

Precautions: Do not mix this product with any other driveway products. Do not dilute. Protective clothing and eyewear should be worn during application. When transporting product make sure lid is securely attached and pail is secured and upright. Do not re-use empty containers. Dispose of in an environmentally acceptable manner. This container is recyclable if cleaned immediately. Do not pour excess product in drains or watercourses. **KEEP FROM FREEZING.** Seal container when not in use.